



Item # \_\_\_\_\_

Job \_\_\_\_\_



***Metroseal 3 is available on Super Erecta and Super Adjustable Super Erecta shelving systems. Metroseal 3 is applied using an exclusive state-of-the-art finishing and coating process that creates an attractive and corrosion-resistant finish. Metroseal 3 is enhanced with built-in Microban® antimicrobial product protection, which protects the Metroseal 3 coating from bacteria, mold, mildew and fungi that cause odors, stains and product degradation.***

- **Exclusive Protection:** Metro's new proprietary epoxy coating now contains Microban® antimicrobial product protection. Microban® protects the epoxy coating from bacteria, mold, mildew and fungi that cause odors, stains and product degradation. The storage system remains cleaner between cleanings.
- **Attractive, Corrosion-Resistant Finish:** Metroseal 3 is an attractive corrosion-resistant finish that protects the shelving against corrosive conditions found in walk-in coolers.
- **Metro® Shelving Systems:** Metroseal 3 is a finish for the world's most popular shelving systems, Super Erecta and Super Adjustable Super Erecta. Both systems provide easy assembly without the use of special tools, adjustability at 1" (25mm) increments, greater air circulation and light penetration, a large selection of accessories, and the versatility to change as your storage needs change. Super Adjustable Super Erecta has the added feature of a unique patented corner release making it the easiest to adjust shelving system ever.
- **Economical:** Metroseal 3 storage shelving is an economical alternative to stainless steel, for use in environments that tend to corrode other metals.
- **12-Year Limited Warranty:** Metroseal 3 is a corrosion-resistant finish for environments which can cause other metals to corrode. Metroseal 3 has a 12-year limited warranty against rust formation.



Super Adjustable Super Erecta



Super Erecta





SUPER ERECTA® AND SUPER ADJUSTABLE SUPER ERECTA®  
METROSEAL 3 SHELVING

**Metroseal 3 Shelves**

Cat. No. Super Adjustable	Cat. No. Super Erecta	Width (in.) (mm)	Length (in.) (mm)	Approx. Pkd. Wt. (lbs.) (kg)	
A1424NK3	1424NK3	14 355	24 610	6	2.7
A1430NK3	1430NK3	14 355	30 760	7	3.2
A1436NK3	1436NK3	14 355	36 914	8	3.6
A1442NK3	1442NK3	14 355	42 1066	9 1/2	4.3
A1448NK3	1448NK3	14 355	48 1219	10 1/2	4.7
A1460NK3	1460NK3	14 355	60 1524	14	6.3
A1472NK3	1472NK3	14 355	72 1825	17	7.7
A1824NK3	1824NK3	18 457	24 610	7	3.2
A1830NK3	1830NK3	18 457	30 760	8	3.6
A1836NK3	1836NK3	18 457	36 914	9 1/2	4.3
A1842NK3	1842NK3	18 457	42 1066	11	5.0
A1848NK3	1848NK3	18 457	48 1219	12	5.4
A1854NK3	1854NK3	18 457	54 1370	14 1/2	6.6
A1860NK3	1860NK3	18 457	60 1524	17	7.7
A1872NK3	1872NK3	18 457	72 1825	20	9.1
A2124NK3	2124NK3	21 530	24 610	8	3.6
A2130NK3	2130NK3	21 530	30 760	9	4.1
A2136NK3	2136NK3	21 530	36 914	11	5.0
A2142NK3	2142NK3	21 530	42 1066	12	5.4
A2148NK3	2148NK3	21 530	48 1219	14	6.4
A2154NK3	2154NK3	21 530	54 1370	16	7.3
A2160NK3	2160NK3	21 530	60 1524	18	8.2
A2172NK3	2172NK3	21 530	72 1825	24	10.9
A2424NK3	2424NK3	24 610	24 610	9	4.1
A2430NK3	2430NK3	24 610	30 760	11	5.0
A2436NK3	2436NK3	24 610	36 914	13	5.9
A2442NK3	2442NK3	24 610	42 1066	15	6.8
A2448NK3	2448NK3	24 610	48 1219	16	7.3
A2454NK3	2454NK3	24 610	54 1370	19	8.6
A2460NK3	2460NK3	24 610	60 1524	21	9.5
A2472NK3	2472NK3	24 610	72 1825	26	11.8
A3036NK3		30 760	36 914	15	6.8
A3048NK3		30 760	48 1219	21	9.5
A3060NK3		30 760	60 1524	26 1/2	11.8
A3072NK3		30 760	72 1825	31	14.0
A3636NK3		36 914	36 914	18	8.2
A3648NK3		36 914	48 1219	23	10.4
A3660NK3		36 914	60 1524	29	13.1
A3672NK3		36 914	72 1825	34 1/2	15.4

**SiteSelect™ Posts**

Cat. No. Metroseal 3	Height*		Approx. Pkd. Wt.	
	(in.)	(mm)	(lbs.)	(kg)
13PK3	14 1/2	368	1	0.5
33PK3	34 1/2	877	2	0.9
54PK3	54 9/16	1386	3	1.4
63PK3	62 9/16	1589	3 1/2	1.6
74PK3	74 5/8	1895	4	1.8
86PK3	86 5/8	2200	5	2.3

\*Height includes leveling bolt and cap.

Every Metroseal 3 shelf and post is backed by a limited 12-year warranty against surface rust formation.



Super Erecta Split Sleeves



Super Adjustable Wedges and Corner Release System

**Important:** When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.



SiteSelect™ Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double-grooved every 8" (203mm) for easy identification.