



TIM CAMPBELL 800-400-7500



Item # _____

Job _____

Metro C5 Pizza Series Heated Holding Cabinet

- **Control:** The C5 Pizza Series controls temperature for safe and hot holding of pizza and other foods. Temperature is displayed on an "always-on" analog thermometer for continuous monitoring of the cabinet temperature, even when turned off or unplugged.
- **Performance:** Rapid heat-up and recovery times are achieved with a thermostatically controlled ducted heating system. All models are Energy Star.
- **Sizes:** C5 Pizza Series cabinets are available in Full Height (74.75") and 1/2 Height (44.75") sizes.
- **Doors:** C5 Pizza Series cabinets are all available with a choice of insulated solid or clear double pane, insulated Low-E, tempered glass doors. Clear doors provide visibility of the contents of the cabinet without the heat loss associated with opening the door. Full Height cabinets are configured with Dutch style doors. All doors lift off and are field reversible.
- **Pass-Thru:** Pass-thru models are available for applications that require access from both the front and the back of the cabinet.
- **Capacity:** C5 Pizza Series cabinets are available configured with Universal Wire Slides or with Wire Shelves. Universal slides hold (2) 16" Pizza boxes front-to-back, 18" x 26" sheet pans, or (2) 12" x 20" steam table pans front-to-back on adjustable 1 1/2" increments. Wire shelves accommodate just about anything including small boxes and odd-sized pans or containers. Wire shelves and universal slides work together and can be intermixed when ordered as accessories.
- **Reliability:** Reliability and durability are designed into all C5 cabinets from the ground up. High-quality components and robust construction provide a long life of service and worry-free use.
- **Top-Mounted Controls:** Ergonomic user-friendly controls are mounted at the top of the cabinet for easier access, better readability, to prevent damage, and to simplify cleaning.
- **Passive Humidity:** An integral water pan system can be used to add humidity to the cabinet environment, improving the quality of food products that require a moist holding environment.
- **Construction:** Available in both stainless steel and aluminum.



Full Height Dutch Clear Doors



Options/Accessories:

- Pizza Wire Shelf (C5-ZSHELF)
- Stainless Steel Legs (C5-SSLEGS)
- Universal Slide Pair (C5-ZUSLIDECPR)
- Right Angle Plug (C5-RTANGPLG)
- Twist Lock Plug (C5-RTWSTPLG)
- Flush Door Latch (C5-LATCHFLUSH)
- Twist Lock Flush Door Latch (C5-LATCHTWST)
- Key Lock Flush Door Latch (C5-LATCHLOCK)
- 6" Casters (C5-6CASTER)
- Rear Rigid Casters (C5-5RDGCSTR)
- Corner Bumpers/Drip Trough (C5-BUMPDRIP)
- Left Hand Hinging (DD3768)
- Control Panel Cover (C5-COVER)

Note: Add an "A" to the end of the cabinet part number when ordering accessories.



Full Height Dutch Solid Doors



1/2 Height Clear Doors



1/2 Height Solid Doors



Specifications

- **Cabinet Material:** Type 304 stainless steel; 20-gauge polished exterior; 22-gauge interior, or .063" aluminum, brushed exterior, natural interior.
- **Insulation:** Full perimeter, 1" thick, high-density fiberglass. R Value = 4.2
- **Casters:** Four casters with 5" donut neoprene wheel, double ball bearing swivel, ball bearing axle, nickel plated, two with brake.
- **Solid Doors:** Fully insulated, double-panel, Type 304, 20-gauge polished exterior, 22-gauge interior stainless steel or .063" aluminum, brushed exterior, natural interior.
- **Hinges:** Self-closing, lift-off, double hinged, with long-life nylon bearings.
- **Gaskets:** High temperature, cabinet mounted, Santoprene gaskets.
- **Latches:** Chrome plated, high-strength magnetic pull latch with lever-action release.
- **Handles:** Four built-in polymer handles.
- **Universal Slides:** Universal wire slides; 1/4" diameter nickel-chrome wire adjustable on 1 1/2" increments. 16-gauge, Type 304, stainless steel vertical standards.
- **Wire Shelves:** Stainless steel wire shelves adjustable on 1 1/2" increments.
- **Cabinet Capacities:**

| Cabinet Size | Universal Slides | | | | Wire Shelves |
|-------------------|------------------|---------------|---------------------|------------------------------------|--------------|
| | Capacity | | | | |
| | Slide Levels | 16" Pizza Box | 18" x 26" Sheet Pan | 12" x 20" x 2 1/2" Steam Table Pan | |
| Full Height/Dutch | 17 | 34 | 17 | 34 | 4 |
| 1/2 Height | 8 | 16 | 8 | 16 | 2 |

*Capacity based on 3" slide spacing, (1) sheet pan per level, (2) 16" pizza boxes per level, or (2) steam table pans per level.

Display and Controls: Analog cabinet thermometer with independent thermostat control knob.

- **Heat Generation System:** Thermostatically controlled 1950 Watt heating element, ball bearing blower motor, and ducted air system.
- **Cord:** 7 1/2' cord with NEMA 5-20P plug. Cord mounted on top (Full Height & Pass Thru) or back (1/2 Height) can be field reversed.
- **Thermal Performance:** 70° F to 200° F operating temperature range.
- **Power Requirements:** 2000 Watts, 120 Volts, 60 Hz., single phase, 20 Amp. Service (16 Amps Draw).


Part Numbers

| FULL HEIGHT CABINETS | | | |
|---------------------------------|-----------|-------------------------|------------------|
| Part Number | Material | Doors | Holding Style |
| C5Z69-SDS-U | Stainless | Dutch Solid | Universal Slides |
| C5Z69-SDS-S | Stainless | Dutch Solid | (4) Shelves |
| C5Z69-SDC-U | Stainless | Dutch Clear | Universal Slides |
| C5Z69-SDC-S | Stainless | Dutch Clear | (4) Shelves |
| C5Z69-NDS-U | Aluminum | Dutch Solid | Universal Slides |
| C5Z69-NDS-S | Aluminum | Dutch Solid | (4) Shelves |
| C5Z69-NDC-U | Aluminum | Dutch Clear | Universal Slides |
| C5Z69-NDC-S | Aluminum | Dutch Clear | (4) Shelves |
| FULL HEIGHT, PASS THRU CABINETS | | | |
| Part Number | Material | Doors | Holding Style |
| C5Z69-SDC-UPDC | Stainless | Dutch Clear/Dutch Clear | Universal Slides |
| C5Z69-SDC-SPDC | Stainless | Dutch Clear/Dutch Clear | (4) Shelves |
| C5Z69-NDC-UPDC | Aluminum | Dutch Clear/Dutch Clear | Universal Slides |
| C5Z69-NDC-SPDC | Aluminum | Dutch Clear/Dutch Clear | (4) Shelves |
| 1/2 HEIGHT CABINETS | | | |
| Part Number | Material | Doors | Holding Style |
| C5Z65-SFS-U | Stainless | Full Solid | Universal Slides |
| C5Z65-SFS-S | Stainless | Full Solid | (2) Shelves |
| C5Z65-SFC-U | Stainless | Full Clear | Universal Slides |
| C5Z65-SFC-S | Stainless | Full Clear | (2) Shelves |
| C5Z65-NFS-U | Aluminum | Full Solid | Universal Slides |
| C5Z65-NFS-S | Aluminum | Full Solid | (2) Shelves |
| C5Z65-NFC-U | Aluminum | Full Clear | Universal Slides |
| C5Z65-NFC-S | Aluminum | Full Clear | (2) Shelves |
| 1/2 HEIGHT, PASS-THRU CABINETS | | | |
| Part Number | Material | Doors | Holding Style |
| C5Z65-SFC-UPFC | Stainless | Full Clear/Full Clear | Universal Slides |
| C5Z65-SFC-SPFC | Stainless | Full Clear/Full Clear | (2) Shelves |
| C5Z65-NFC-UPFC | Aluminum | Full Clear/Full Clear | Universal Slides |
| C5Z65-NFC-SPFC | Aluminum | Full Clear/Full Clear | (2) Shelves |

Note: Add an "A" to the end of the cabinet part number when ordering accessories.

Dimensions

All cabinets are 28" wide and 38 1/4" deep (Pass-Thru are 40 1/2" deep)



Metro Heated cabinets are for hot food holding applications only.