



TIM CAMPBELL 800-400-7500

Item # \_\_\_\_\_

Job \_\_\_\_\_

## SUPER ERECTA SHELF® STEM CASTER CARTS – SOLID SHELVES

- **Stem Caster Carts** combine Super Erecta Shelf® solid shelving features with the mobility of stem casters to provide a high-quality, strong and versatile material handling cart.
- **Variety of Casters Available:** Select the caster that allows the right combination of rollability and maneuverability to suit your requirements. Casters are available in swivel, rigid or brake types. All Metro casters are non-marking and come complete with a 3 1/2" donut bumper. Refer to sheet #11.20 for additional caster information.
- **Strength:** Two-fold thickness of 18-gauge steel forms 1/8" raised edges on all four sides of the shelving. This ship's edge gives all-around rigidity and high-strength. Sturdy aluminum castings firmly lock the corners to the posts.
- **Sanitary:** The raised ship's edge on all four sides and at the corners contains spillage, minimizes contamination and permits easier clean-up. Embossed or louvered/embossed shelf designs allow air circulation under packages and containers.
- **Fast, Secure Assembly:** Post has rolled, circular grooves along its entire height at 1" (25mm) intervals. A patented, tapered split sleeve (plastic or aluminum) snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves providing a positive lock. Cart is assembled in minutes without the use of nuts or bolts and without the use of any special tools.
- **Adjustability:** Shelves can be adjusted at 1" (25mm) intervals along the entire height of the post.





SUPER ERECTA SHELF®  
STEM CASTER CARTS –  
SOLID SHELVES

## Dimensions

**Standard Units:**

Consist of four shelves, posts, plastic split sleeves\*, donut bumpers and designated casters.


**With Galvanized Flat Solid Shelves & Plated Posts**

62" (1575mm) Posts — Overall Height 68" (1730mm)

| Solid Shelf    |      |                 |      | Cat. No. with Casters |                   |             |                     |
|----------------|------|-----------------|------|-----------------------|-------------------|-------------|---------------------|
| Width<br>(in.) | (mm) | Length<br>(in.) | (mm) | Four<br>5M            | Two 5M<br>Two 5MB | Four<br>5MP | Two 5MP<br>Two 5MPB |
| 18             | 455  | 36              | 910  | F336AG                | F336BG            | F336DG      | F336EG              |
| 18             | 455  | 48              | 1220 | F356AG                | F356BG            | F356DG      | F356EG              |
| 18             | 455  | 60              | 1525 | F366AG                | F366BG            | F366DG      | F366EG              |
| 21             | 530  | 36              | 910  | F436AG                | F436BG            | F436DG      | F436EG              |
| 21             | 530  | 48              | 1220 | F456AG                | F456BG            | F456DG      | F456EG              |
| 21             | 530  | 60              | 1525 | F466AG                | F466BG            | F466DG      | F466EG              |
| 24             | 610  | 36              | 910  | F536AG                | F536BG            | F536DG      | F536EG              |
| 24             | 610  | 48              | 1220 | F556AG                | F556BG            | F556DG      | F556EG              |
| 24             | 610  | 60              | 1525 | F566AG                | F566BG            | F566DG      | F566EG              |

**Posts**

| Height<br>(in.)                | (mm) | Approx.<br>Pkd. Wt<br>(lbs.)  | (kg) | Cat. No.<br>Plated |
|--------------------------------|------|-------------------------------|------|--------------------|
| 13 <sup>7</sup> / <sub>8</sub> | 352  | 1                             | 0.5  | 13UP               |
| 33 <sup>7</sup> / <sub>8</sub> | 835  | 2                             | 0.9  | 33UP               |
| 54                             | 1370 | 3                             | 1.4  | 54UP               |
| 62                             | 1575 | 3 <sup>1</sup> / <sub>2</sub> | 1.6  | 63UP               |
| 74                             | 1880 | 4                             | 1.8  | 74UP               |
| 86                             | 2185 | 5                             | 2.3  | 86UP               |



**SiteSelect™ Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double-grooved every 8" (203mm) for easy identification.**

\* Aluminum split sleeves are recommended when unit will be towed, transported over the road or otherwise subjected to vibration or jolting. To order, see catalog sheet #10.06 or price list.

**Load Rating:** 3 times the caster load rating, or not to exceed 800 lbs. (363 kg) per cart.

## To Order By Components

1. Order shelves from catalog sheet #10.20 or price list. (Will be packed with plastic split sleeves.\*)
2. Order stem casters from catalog sheet #11.20 or price list. Donut bumper comes with caster.
3. Order posts from table at left. Except for rigid casters, posts are shipped assembled with caster and donut bumper.

**IMPORTANT:** When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.