TIM CAMPBELL 800-400-7500



Item#	

ob_____





Garment Rack: Wall Mount

GARMENT RACKS

Type 304 Stainless Steel and Proven Super Erecta[®] Construction throughout.

- Floor-Mountable Upright and Wall Mount versions available.
- Open wire construction promotes laminar air flow.
- Electro-polished, Type 304 Stainless Steel hangers are included. Hangers are spaced at 3" (76mm) intervals.
- Unique hanger capture mechanism provides theft deterrance.
- Easy to assemble.
- Adjustable stainless steel triangular foot plates provided for floor mounting.
- Available in several sizes to suit your requirements.
- Upright unit is non-conductive, but can be made conductive with the addition of aluminum split sleeves (9986Z).

					App	rox.		App	rox.
Width/Length			Cat. No.	Pkd	. Wt.	Cat. No.	Pkd.	. Wt.	
	(in.)	(mm)	# of Hangers	Upright	(lbs.)	(kg.)	Wall Mount	(lbs.)	(kg.)
	24x36	610x915	11	GRU2436S	27	12.25	GRW2436S	20	9
	24x48	610x1220	15	GRU2448S	36	16.25	GRW2448S	221/2	10.2
	24x60	610x1525	19	GRU2460S	45	20.5	GRW2460S	271/2	12.5
	24x72	610x1825	23	GRU2472S	54	24.5	GRW2472S	32	14.5

Job

METRO®

GOWNING BENCH

GOWNING BENCH

Type 304 stainless steel, H.D. Super™ posts and proven Super Erecta construction throughout.

- Heavy duty, solid top bench provides a sturdy and comfortable gowning fixture.
 All benches are 18" (457mm) tall.
- Top is manufactured from 14 gauge, Type 304 stainless steel.
- Adjustable stainless steel foot plates provide for floor mounting.
- Available in several lengths to suit your requirements.
- Unit is non-conductive but can be made conductive with the addition of H.D. Aluminum Split Sleeves (9986HZ).



Width	n/Length		Approx. Pkd. Wt.	
(in.)	(mm)	Cat. No.	(lbs.)	(kg.)
16x36	610x915	GB1636S	471/2	21.5
16x48	610x1220	GB1648S	55	25
16x60	610x1525	GB1660S	621/2	28.4
16x72	610x1825	GB1672S	70	31.8