TIM CAMPBELL 800-400-7500



Job	

ROLL-IN REFRIGERATOR RACKS Model RF Series

- Material: Special design, natural finish, highstrength, extruded aluminum (6063-T6 alloy).
- **Rugged:** Aircraft-riveted construction throughout . . . means additional strength.
- Pass-Thru Design: Can be loaded on one side and unloaded from the other for maximum efficiency and convenience.
- Sized To Fit Refrigerator: Rack rolls directly into refrigerator for quick and easy storage. You save valuable handling time and expensive labor costs.
- Lightweight and Freewheeling
- Sanitary: Easy to clean.
- Rapid Cooling Saves Energy



METRO MOBILE ROLL-IN REFRIGERATOR RACKS



Specifications

Materials: Special design, natural finish, high-strength, extruded aluminum (6063-T6 alloy).


Construction: Pass-thru design, aircraft-riveted construction throughout.

Corner Posts: 1½" x 1½" x 1½" angle-shape. (Except RF20N, RF29N: 1"x 1½" x ½")

Top & Bottom: $1\frac{1}{2}$ " x $1\frac{1}{2}$ " x $1\frac{1}{2}$ " angle-shape riveted to four corner posts. (Bottom closed on RF78N.)

Casters: Two A5L on back — 5" ball bearing swivel, self-lubricating axle, rubber-wheeled, zinc-plated, bolted to full-length 14-gauge channel to bottom frame. Two A5LB on front — same as above with wheel brake. (Except two B5DN and two B5DNB on RF78N.)

Slides: RF3N and RF23N, .060" x $1\frac{1}{2}$ " bulb-tipped angle. RF13N and RF20N, .060" x $\frac{1}{2}$ " x $1\frac{1}{2}$ " extruded aluminum channel. RF29N, 18-gauge x $\frac{1}{2}$ " x $1\frac{1}{2}$ " stainless steel channel. RF78N,12 sets extruded varislides, adjustable on $1\frac{1}{2}$ " centers, 3" minimum slide spacing.



Dimensions

Without Bumper				With A33 Bumper													
	(A)	(B		(C)		(B)		((Sli	de				ping		
Н	leight	Wic	dth	Dep	oth	Wid	lth	De	pth	Spa	ıcing	Pan	Capacity	W∈	eight		
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	No.	Size (in.)	(lbs.)	(kg)	Cat. No.	
64	1600	211/4	540	26	660	231/4	590	28	710	11/2	38	36	18x26	44	20	RF13N	
64	1600	21%	543	26	660	23%	595	28	710	3	76	18	18x26	55	25	RF3N	
64	1600	21%	543	26	660	23%	595	28	710	5	127	11	18x26	43	19	RF23N	
641/2	1610	24%	630	26	660	26%	670	28	710	See	Note 1	See	Note 1	92	41	RF78N	

NOTE: Swivel casters, two with brakes, are standard on the units listed above.

NOTE 1: Pan capacity with 12 sets of slides on 41/2" centers.

Accessories

Description	Model
Gray Continuous Bumper	A33RD
Gray Corner Bumpers	A37
Floor Lock with B5DN/B5DNB Casters Only	A71
Extra Vari-Slides for RF78N	A121

2 per slide	1 p	er slide	
Size (in.)	No.	Size (in.)	
107/8x193/4	12	15x20	
111/x20	12	18x26	
12x18	12	20x20	
12x20	12	20x22	
13x18	12	20x24	
14x18			
	10%x19¾ 11%x20 12x18 12x20 13x18	Size (in.) No. 107/8x193/4 12 111/8x20 12 12x18 12 12x20 12 13x18 12	Size (in.) No. Size (in.) 10½x19¾ 12 15x20 11½x20 12 18x26 12x18 12 20x20 12x20 12 20x22 13x18 12 20x24