

TIM CAMPBELL 800-400-7500

Item #

Job

STARSYS[™] SYSTEM MOBILE WORKCENTERS

Metro Starsys[™] flexible lab furniture is a mobilebased, highly-adaptive system, that enhances lab productivity and space efficiency by empowering the end user with the ability to easily reconfigure and move units around the lab.

The Starsys Modular System creates flexible space. No matter what you need — open, closed, short, tall, mobile units, stationary elements, preconfigured workcenters — Starsys has the elements for you.

With Starsys, you choose from an array of modular units to fit the space and work specifications. It's that easy. And that flexible.

Benefits:

- Facilitates fast, efficient product or furniture installation.
- The ability to easily reconfigure lab furniture layout as needs change.
- The ability to easily reconfigure unit design.
- Flexibility to design a storage solution to exact needs.
- Corrosion-proof polymer components for a contamination-free product.
- Durable, easy-to-clean, polymer enclosures that won't chip, peel, dent, or rust ever.
- Rigid anodized aluminum and metal substructure, combined with advanced polymers, provides a robust and stable work environment for even the most sensitive equipment.
- A high level of organization.
- Easy access to supplies.
- Greater storage density in a smaller footprint.





Mobile WorkCenter with Stainless Steel Top

Mobile WorkCenter with Blank Bracket Option





Specifications

Starsys[™] epoxy resin worksurfaces are generally 1" (25mm) thick. Unless otherwise specified, worksurfaces are monolithic and molded from a modified epoxy resin, with a uniform mixture throughout the top forming a thermosetting material. Back or side splashes are shipped separately and affixed on site to epoxy top. Worksurfaces have a smooth, non-glare finish.

Laminate top material is 1¹/₈" (29mm) Chip Core with HPL. Laminate thickness is .04" (1.0mm). Phenolic backer thickness is .02" (0.5mm).

Refer to Starsys chemical resistance report for a complete description of Starsys material specifications. A copy of the report can be found at www.metro.com or by contacting your local Metro representative.

Drawers

Standard Drawers

Inside Dimensions			Weight		
Description	Height/Widt (in.)	h/Length (mm)	Capaci (Ibs.)	ity (kg)	Cat. No.
3" (76mm)	2 ³ / ₈ x16 ³ / ₈ x15 ⁷ / ₈	60x416x403	25	11.4	SXS3
4.5" (114mm)	3 ⁷ / ₈ x16 ³ / ₈ x15 ⁷ / ₈	98x416x403	25	11.4	SXS4.5
6" (152mm)	5 ³ / ₈ x16 ¹ / ₄ x15 ³ / ₄	136x413x400	40	18.2	SXS6
7.5" (191mm)	6 ⁷ / ₈ x16 ¹ / ₄ x15 ³ / ₄	175x413x400	40	18.2	SXS7.5
9" (230mm)	8 ³ / ₈ x16 ¹ / ₄ x15 ³ / ₄	213x413x400	40	18.2	SXS9
10.5" (267mm)	9 ⁷ / ₈ x16 ¹ / ₄ x15 ³ / ₄	251x413x400	40	18.2	SXS10.5
12" (305mm)	11 ³ / ₈ ×16 ¹ / ₄ ×15 ³ / ₄	289x413x400	40	18.2	SXS12

Heavy-Duty Drawers

	Inside Dimensions		Mobile WorkCenters		Weight Capacity Stationary		Mobile WorkCenters	
(in.)	(mm)	(lbs.)	(kg)	(lbs.)	(kg)	(lbs.)	(kg)	Cat. No.
2 ¹ / ₄ x16 ³ / ₈ x19 ³ / ₁₆	57x416x487	100	45.4	100	45.4	100	45.4	SXS3HD
5 ¹ / ₄ x16 ³ / ₈ x19 ³ / ₁₆	133x416x487	100	45.4	100	45.4	100	45.4	SXS6HD
8 ¹ / ₄ x16 ³ / ₈ x19 ³ / ₁₆	209x416x487	100	45.4	100	45.4	100	45.4	SXS9HD
11 ¹ / ₄ x16 ³ / ₈ x19 ³ / ₁₆	285x416x487	100	45.4	100	45.4	100	45.4	SXS12HD
2 ¹ / ₈ x36 ¹ / ₄ x19 ³ / ₁₆	54x920x487	150	68.0	150	68.0	150	68.0	SXD3HD
5 ¹ / ₈ x36 ¹ / ₄ x19 ³ / ₁₆	130x920x487	150	68.0	150	68.0	150	68.0	SXD6HD
8 ¹ / ₈ x36 ¹ / ₄ x19 ³ / ₁₆	206x920x487	150	68.0	150	68.0	150	68.0	SXD9HD
11 ¹ / ₈ x36 ¹ / ₄ x19 ³ / ₁₆	283x920x487	150	68.0	150	68.0	150	68.0	SXD12HD
	$\begin{array}{c} & \text{Height/Wid} \\ \hline \\ & 2^{1/4} \times 16^{3/8} \times 19^{3/16} \\ 5^{1/4} \times 16^{3/8} \times 19^{3/16} \\ 8^{1/4} \times 16^{3/8} \times 19^{3/16} \\ 11^{1/4} \times 16^{3/8} \times 19^{3/16} \\ \hline \\ & 2^{1/8} \times 36^{1/4} \times 19^{3/16} \\ 5^{1/8} \times 36^{1/4} \times 19^{3/16} \\ 8^{1/8} \times 36^{1/4} \times 19^{3/16} \\ \end{array}$	$\begin{array}{c} & {\mbox{Height/Width/Length} \\ (in.) & (mm) \\ \hline \\ 2^{1/}_4 \times 16^3/_8 \times 19^3/_{16} & 57 \times 416 \times 487 \\ 5^{1/}_4 \times 16^3/_8 \times 19^3/_{16} & 133 \times 416 \times 487 \\ 8^{1/}_4 \times 16^3/_8 \times 19^3/_{16} & 209 \times 416 \times 487 \\ 11^{1/}_4 \times 16^3/_8 \times 19^3/_{16} & 285 \times 416 \times 487 \\ \hline \\ 2^{1/}_8 \times 36^{1/}_4 \times 19^3/_{16} & 54 \times 920 \times 487 \\ 5^{1/}_8 \times 36^{1/}_4 \times 19^3/_{16} & 130 \times 920 \times 487 \\ 8^{1/}_8 \times 36^{1/}_4 \times 19^3/_{16} & 206 \times 920 \times 487 \\ \end{array}$	Height/Width/Length (in.) with Overhe (lbs.) 2 ¹ / ₄ x16 ³ / ₈ x19 ³ / ₁₆ 57x416x487 100 5 ¹ / ₄ x16 ³ / ₈ x19 ³ / ₁₆ 133x416x487 100 8 ¹ / ₄ x16 ³ / ₈ x19 ³ / ₁₆ 209x416x487 100 11 ¹ / ₄ x16 ³ / ₈ x19 ³ / ₁₆ 285x416x487 100 2 ¹ / ₈ x36 ¹ / ₄ x19 ³ / ₁₆ 54x920x487 150 5 ¹ / ₈ x36 ¹ / ₄ x19 ³ / ₁₆ 54x920x487 150 8 ¹ / ₈ x36 ¹ / ₄ x19 ³ / ₁₆ 206x920x487 150	$\begin{array}{c c} \mbox{Height/Width/Length} & \mbox{with Overhead Cabinets} \\ \mbox{(lbs.)} & \mbox{(lbs.)} & \mbox{(lbs.)} \\ \hline \\ 2^{1/4}x16^3/_8x19^3/_{16} & 57x416x487 & 100 & 45.4 \\ 5^{1/4}x16^3/_8x19^3/_{16} & 133x416x487 & 100 & 45.4 \\ 8^{1/4}x16^3/_8x19^3/_{16} & 209x416x487 & 100 & 45.4 \\ 11^{1/4}x16^3/_8x19^3/_{16} & 285x416x487 & 100 & 45.4 \\ \hline \\ & & & & & & & \\ 2^{1/6}x36^{1/4}x19^3/_{16} & 54x920x487 & 150 & 68.0 \\ 5^{1/6}x36^{1/4}x19^3/_{16} & 130x920x487 & 150 & 68.0 \\ 8^{1/6}x36^{1/4}x19^3/_{16} & 206x920x487 & 150 & 68.0 \\ \hline \end{array}$	$\begin{array}{c c} \mbox{height/Width/Length} & \mbox{Mobile WorkCenters} & \mbox{Static} \\ \mbox{with Overhead Cabinets} & \mbox{(hg)} & $	$\begin{array}{c c} \mbox{Inside Dimensions}\\ \mbox{Height/Width/Length}\\ \mbox{(in.)} \mbox{(mm)} \mbox{(lbs.)} \mbox{(kg)} \mbox{Moverhead Cabinets}\\ \mbox{(lbs.)} \mbox{(kg)} \mbox{(lbs.)} \mbox{(lbs.)} \mbox{(kg)} \mbox{(lbs.)} \mbox{(lbs.)} \mbox{(lbs.)} \mbox{(kg)} \mbox{(lbs.)} ($	$\begin{array}{c c} \mbox{Inside Dimensions}\\ \mbox{(in.)} & \mbox{(mm)} & \mbox{Mobile WorkCenters} & \mbox{Stationary} & \mbox{Applications} & \mbox{Applicationary} & \mbox{Mobile Work} & \mbox{Applicationary} & \mbox{Mobile Work} & \mbox{(lbs.)} $	$\begin{array}{c c c c c c c c c c c c c c c c c c c $

*Note: Single wide 12" (305mm) file drawers include hanging file accessory.

To specify color for drawer pull, order following catalog number for each drawer:

Description	Cat. No.
Dark Taupe	SXDP-TP
Slate Blue	SXDP-BL
Jade	SXDP-GR
Mauve	SXDP-RD
Code Blue	SXDP-CB
Yellow	SXDP-YL
Black	SXDP-BK
Red	SXDP-RE

Note: 2 drawer pulls are required for double-wide heavy-duty drawers.

Drawer and Door Label Kit

10 per package. 1" (25mm) H. x 16" (406mm) L. Cat. No. **SXLABKIT**





Overhead Cabinets*

Cabinets include inner panels and mounting rails. Refer to shaded door catalog numbers (pages 5 & 6) for recommended overhead doors.

		Height/Depth			
Description	Overall I (in.)	Dimensions (mm)	Inside I (in.)	Dimensions (mm)	Cat. No.
Single-Wide Cabinets	(iii.)	(1111)	(iii.)	(1111)	Cal. NO.
24" (610mm)	26 ³ / ₈ x13 ¹ / ₂ x21 ¹ / ₂	670x343x546	24 ⁵ /8x12x17	625x341x432	SXSOH24F
27" (686mm)	29 ³ / ₈ x13 ¹ / ₂ x21 ¹ / ₂	746x343x546	27 ⁵ / ₈ x12x17	702x341x432	SXSOH27F
30" (760mm)	32 ³ / ₈ x13 ¹ / ₂ x21 ¹ / ₂	822x343x546	30 ⁵ / ₈ x12x17	778x341x432	SXSOH30F
33" (838mm)	35 ³ / ₈ x13 ¹ / ₂ x21 ¹ / ₂	898x343x546	33 ⁵ /8x12x17	854x341x432	SXSOH33F
36" (914mm)	38 ³ / ₈ x13 ¹ / ₂ x21 ¹ / ₂	973x343x546	36 ⁵ /8x12x17	930x341x432	SXSOH36F
48" (1219mm)	50 ³ /8x13 ¹ /2x21 ¹ /2	1279x343x546	48⁵/₀x12x17	1235x341x432	SXSOH48
Double-Wide Cabinets					
24" (610mm)	26 ³ /8x13 ¹ /2x41 ³ /8	670x343x1051	24 ⁵ /8x10x36 ³ /4	625x254x933	SXDOH24
27" (686mm)	29 ³ /8x13 ¹ /2x41 ³ /8	746x343x1051	27 ⁵ /8x10x36 ³ /4	702x254x933	SXDOH27
30" (760mm)	32 ³ /8x13 ¹ /2x41 ³ /8	822x343x1051	30 ⁵ /8x10x36 ³ /4	778x254x933	SXDOH30
33" (838mm)	35 ³ / ₈ x13 ¹ / ₂ x41 ³ / ₈	898x343x1051	33 ⁵ /8x10x36 ³ /4	854x254x933	SXDOH33
36" (914mm)	38 ³ / ₈ x13 ¹ / ₂ x41 ³ / ₈	973x343x1051	36 ⁵ /8x10x36 ³ /4	930x254x933	SXDOH36
48" (1219mm)	50 ³ / ₈ x13 ¹ / ₂ x41 ³ / ₈	1279x343x1051	48 ⁵ /8x10x36 ³ /4	1235x254x933	SXDOH48
Shelves for Single-Wide C	abinets †				
Wire Shelf	1 ³ / ₈ x11x17 ¹⁵ / ₁₆	35x279x456			SXSOHWE
Poly Shelf	1 ¹ / ₂ x12x18	38x305x457			SXSOHPS
Shelves for Double-Wide	Cabinets † †				
Wire Shelf	1 ³ /8x11x36 ¹¹ /16	35x279x932			SXDOHWE
Poly Shelf	1 ¹ / ₂ x12x37 ⁵ / ₈	38x305x956			SXDOHPS

t Load rating for single-wide shelves, both wire and poly, is 60 lbs. (27kg).
t Load rating for double-wide shelves, both wire and poly, is 120 lbs. (54kg).
* Triple-wide overhead cabinets are only offered as part of Mobile WorkCenter offering. Contact your Metro representative for more information.

Overhead Accessories

Height/Depth/Width					
Description	(in.)	(mm)	Cat. No.		
Overhead Light for Single-Wide Cabinets	1.50x5.82x19.75	38x148x502	SXSOHL		
Overhead Light for Double-Wide Cabinets	1.50x5.82x39.55	38x148x1005	SXDOHL		
Overhead Light for Triple-Wide Cabinets	1.50x5.82x59.35	38x148x1507	SXTOHL		
Overhead Light (No Valance)	1.32x4.63x14.25	34x118x362	SXOHLT		
Single-Wide Mounting Rails (pair)	2.75x.312x21.375	69x8x542	SXOHWB-22		
Double-Wide Mounting Rails (pair)	2.75x.312x41.188	69x8x1046	SXOHWB-42		
Overhead Filler Strip	2.875x.125x49.75	73x3x1264	SXOHFLR-49		
Overhead Filler Strip	2.875x.125x63.00	73x3x1600	SXOHFLR-63		

Drawer and Door Label Kit

10 per package. 1" (25mm) H. x 16" (406mm) L. Cat. No. SXLABKIT



Single-Wide Overhead Cabinet with Solid Door



Double-Wide Overhead Cabinet with Wire Shelves (2) and Locking, Clear Door



Double-Wide Overhead Cabinet with Polymer Shelves and Locking, Clear Door

Refer to pages 5 and 6 for door options



Mobile WorkCenter with

*Base unit working height is

equal to Base interior height +9" [229mm] (based on 5"

Overhead exterior height is equal to Overhead interior height +2.5" [64mm]

Reagent Shelving

[127mm] casters)

Refer to page 3 for overhead cabinet options

Additional caster options are available through the Metro Starsys Configurator

or by contacting your Metro representative.

LAB SOLUTIONS

Mobile WorkCenter Overhead Cabinet Support

Description	Cat. No.
Lateral Members	
Overhead Structure Single Wide Mobile WorkCenter	SXSMWOHB
Overhead Structure Double Wide Mobile WorkCenter	SXDMWOHB
Ov erhead Structure Triple Wide Mobile WorkCenter	SXTMWOHB
Overhead Structure Single-Kneewell Mobile WorkCenter	SXKMWOHB
Vertical Supports	
24" (610mm) Base Interior with 24" (610mm) Overhead Interior	SXMWUP24-24
24" (610mm) Base Interior with 27" (686mm) Overhead Interior	SXMWUP24-27
24" (610mm) Base Interior with 30" (762mm) Overhead Interior	SXMWUP24-30
24" (610mm) Base Interior with 33" (838mm) Overhead Interior	SXMWUP24-33
27" (686mm) Base Interior with 24" (610mm) Overhead Interior	SXMWUP27-24
27" (686mm) Base Interior with 27" (686mm) Overhead Interior	SXMWUP27-27
27" (686mm) Base Interior with 30" (762mm) Overhead Interior	SXMWUP27-30
30" (762mm) Base Interior with 24" (610mm) Overhead Interior	SXMWUP30-24
30" (762mm) Base Interior with 27" (686mm) Overhead Interior	SXMWUP30-27
33" (838mm) Base Interior with 24" (610mm) Overhead Interior	SXMWUP33-24
Overhead Cabinet and Shelving Combination — Vertical Supports	
24" (610mm) Base 24" (610mm) Overhead Interior & Slotted Inserts	SXMWUP24Q-24
24" (610mm) Base 27" (686mm) Overhead Interior & Slotted Inserts	SXMWUP24Q-27
24" (610mm) Base 30" (762mm) Overhead Interior & Slotted Inserts	SXMWUP24Q-30
24" (610mm) Base 33" (838mm) Overhead Interior & Slotted Inserts	SXMWUP24Q-33
27" (686mm) Base 24" (610mm) Overhead Interior & Slotted Inserts	SXMWUP27Q-24
27" (686mm) Base 27" (686mm) Overhead Interior & Slotted Inserts	SXMWUP27Q-27
27" (686mm) Base 30" (762mm) Overhead Interior & Slotted Inserts	SXMWUP27Q-30
30" (762mm) Base 24" (610mm) Overhead Interior & Slotted Inserts	SXMWUP30Q-24
30" (762mm) Base 27" (686mm) Overhead Interior & Slotted Inserts	SXMWUP30Q-27
33" (838mm) Base 24" (610mm) Overhead Interior & Slotted Inserts	SXMWUP33Q-24
Contact the Metro Starsys team for dimension and packaged weight information.	

Mobile WorkCenter Shelving Support

Description	Cat. No.
Shelving Options	
Shelf Assembly — Single width	SXSMWSHF
Shelf Assembly — Double width	SXDMWSHF
Shelf Assembly — Triple width	SXTMWSHF
Shelf Assembly — Single — Kneewell — Single	SXKMWSHF
Lateral Member	
Cross Member — Single width	SXSMWSB
Cross Member — Double width	SXDMWSB
Cross Member — Triple width	SXTMWSB
Cross Member — Single — Kneewell — Single	SXKMWSB
Vertical Supports with Slotted Inserts	
24" (610mm) Base Interior with Slotted Inserts	SXMWUP24Q
27" (686mm) Base Interior with Slotted Inserts	SXMWUP27Q
30" (762mm) Base Interior with Slotted Inserts	SXMWUP30Q
33" (838mm) Base Interior with Slotted Inserts	SXMWUP33Q
Contact the Matra Starous team for dimension and peakaged weight information	

Contact the Metro Starsys team for dimension and packaged weight information.

Caster Options

Description	Cat. No.
3" (76mm) Stabilizer/Leveling Caster	B3N-AS
3" (76mm) Total Lock	B3P-TL
5" (127mm) Poly Total Lock Caster	B5PC-TL

3" Total-Lock Caster:

Utilize 3" total-lock plate casters for limited mobile applications or when additional storage area is required.



5" Total-Lock, All-Polymer Caster: Recommended for corrosive environments. All-polymer total-lock plate caster is an economical alternative to stainless casters.



Stabilizer/Leveling Caster:

Recommended for applications where benchtop equipment demands unit stability and/or a level worksurface. Engage caster foot for stability, release for mobility.



Starsys Carts are built to exact customer specifications, therefore, they are non-cancelable, non-returnable.

TIM CAMPBELL 800-400-7500



Starsys[™] Doors — Solid

	Ноі	ght	•••••
Description		(mm)	Cat. No.
Center-Closing Locking Door, 90°	24	610	SXDRB24C1BS
Center-Closing Non-Locking Door, 90°	24	610	SXDRB24C1NS
Center-Closing Non-Locking Door, Top-Mounted, 90°	24	610	SXDRB24C1US
Center-Closing Locking Door, Top-Mounted, 90°	24	610	SXDRB24C1TS
Center-Closing Locking Door, 270°	24	610	SXDRB24C2BS
Center-Closing Non-Locking Door, 270°	24	610	SXDRB24C2NS
Center-Closing Non-Locking Door, Top-Mounted, 270	° 24	610	SXDRB24C2US
Center-Closing Locking Door, Top-Mounted, 270°	24	610	SXDRB24C2TS
Left-Hinged Locking Door, 90°	24	610	SXDRB24L1BS
Left-Hinged Non-Locking Door, 90°	24	610	SXDRB24L1NS
Left-Hinged Non-Locking Door, Top-Mounted, 90°	24	610	SXDRB24L1US
Left-Hinged Locking Door, Top-Mounted, 90°	24	610	SXDRB24L1TS
Left-Hinged Locking Door, 270°	24	610	SXDRB24L2BS
Left-Hinged Non-Locking Door, 270°	24	610	SXDRB24L2NS
Left-Hinged Non-Locking Door, Top-Mounted, 270°	24	610	SXDRB24L2US
Left-Hinged Locking Door, Top-Mounted, 270°	24	610	SXDRB24L2TS
Right-Hinged Locking Door, 90°	24	610	SXDRB24R1BS
Right-Hinged Non-Locking Door, 90°	24	610	SXDRB24R1NS
Right-Hinged Non-Locking Door, Top-Mounted, 90°	24	610	SXDRB24R1US
Right-Hinged Locking Door, Top-Mounted, 90°	24	610	SXDRB24R1TS
Right-Hinged Locking Door, 270°	24	610	SXDRB24R2BS
Right-Hinged Non-Locking Door, 270°	24	610	
Right-Hinged Non-Locking Door, Top-Mounted, 270°	24	610	
Right-Hinged Locking Door, Top-Mounted, 270°	24	610	SXDRB24R2TS
Center-Closing Locking Door, 90°	27	686	SXDRB27C1BS
Center-Closing Non-Locking Door, 90°	27	686	
Center-Closing Non-Locking Door, Top-Mounted, 90°	27	686	
Center-Closing Locking Door, Top-Mounted, 90°	27	686	
Center-Closing Locking Door, 270°	27	686	
Center-Closing Non-Locking Door, 270°	27	686	
Center-Closing Non-Locking Door, Top-Mounted, 270		686	
Center-Closing Locking Door, Top-Mounted, 270°	27	686	
Left-Hinged Locking Door, 90°	27	686	SXDRB27L1BS
Left-Hinged Non-Locking Door, 90°	27	686	SXDRB27L1DS
Left-Hinged Non-Locking Door, Top-Mounted, 90°	27	686	SXDRB27L1US
Left-Hinged Locking Door, Top-Mounted, 90°	27	686	SXDRB27L1TS
Left-Hinged Locking Door, 270°	27	686	SXDRB27L2BS
Left-Hinged Non-Locking Door, 270°	27	686	SXDRB27L2DS
Left-Hinged Non-Locking Door, Top-Mounted, 270°	27	686	SXDRB27L2US
Left-Hinged Locking Door, Top-Mounted, 270°	27	686	SXDRB27L2TS
Right-Hinged Locking Door, 90°	27	686	SXDRB27R1BS
Right-Hinged Non-Locking Door, 90°	27	686	
Right-Hinged Non-Locking Door, Top-Mounted, 90°	27	686	
Right-Hinged Locking Door, Top-Mounted, 90°	27	686	SXDRB27R1TS
Right-Hinged Locking Door, 270° Right-Hinged Non-Locking Door, 270°	27 27	686 686	
Right-Hinged Non-Locking Door, Top-Mounted, 270°	27	686	SXDRB27R2US
Right-Hinged Locking Door, Top-Mounted, 270°	27	686	SXDRB27R2TS
Center-Closing Locking Door, 90°	30	760	SXDRB30C1BS
Center-Closing Non-Locking Door, 90° Center-Closing Non-Locking Door, Top-Mounted, 90°	30 30	760	SXDRB30C1NS SXDRB30C1US
Center-Closing Non-Locking Door, Top-Mounted, 90°	30	760	
Center-Closing Locking Door, 270°	30	760	
Center-Closing Non-Locking Door, 270°	30	760	
Center-Closing Non-Locking Door, Top-Mounted, 270°			SXDRB30C2US
Center-Closing Locking Door, Top-Mounted, 270°	30	760	SXDRB30C2TS
Left-Hinged Locking Door, 90°	30	760	SXDRB30L1BS
Left-Hinged Non-Locking Door, 90°	30	760	SXDRB30L1NS
Left-Hinged Non-Locking Door, Top-Mounted, 90°	30	760	SXDRB30L1US
Left-Hinged Locking Door, Top-Mounted, 90°	30	760	SXDRB30L1TS

Description	He	ight	Cat. No.
Left-Hinged Locking Door, 270°	30	(mm) 760	SXDRB30L2BS
Left-Hinged Non-Locking Door, 270°	30	760	SXDRB30L2NS
Left-Hinged Non-Locking Door, Top-Mounted, 270°	30	760	SXDRB30L2US
Left-Hinged Locking Door, Top-Mounted, 270°	30	760	SXDRB30L2TS
Right-Hinged Locking Door, 90°	30	760	SXDRB30R1BS
Right-Hinged Non-Locking Door, 90°	30	760	
Right-Hinged Non-Locking Door, Top-Mounted, 90°	30	760	SXDRB30R1US
Right-Hinged Locking Door, Top-Mounted, 90°	30	760	SXDRB30R1TS
Right-Hinged Locking Door, 270°	30	760	SXDRB30B2BS
Right-Hinged Non-Locking Door, 270°	30	760	
Right-Hinged Non-Locking Door, Top-Mounted, 270°	30	760	SXDRB30R2US
Right-Hinged Locking Door, Top-Mounted, 270°	30	760	SXDRB30R2TS
Center-Closing Locking Door, 90°	33	838	SXDRB33C1BS
Center-Closing Non-Locking Door, 90°	33	838	SXDRB33C1NS
Center-Closing Non-Locking Door, Top-Mounted, 90°	33	838	SXDRB33C1US
Center-Closing Locking Door, Top-Mounted, 90°	33	838	SXDRB33C1TS
Center-Closing Locking Door, 270°	33	838	SXDRB33C2BS
Center-Closing Non-Locking Door, 270°	33	838	SXDRB33C2NS
Center-Closing Non-Locking Door, Top-Mounted, 270)°33	838	
Center-Closing Locking Door, Top-Mounted, 270°	33	838	SXDRB33C2TS
Left-Hinged Locking Door, 90°	33	838	SXDRB33L1BS
Left-Hinged Non-Locking Door, 90°	33	838	SXDRB33L1NS
Left-Hinged Non-Locking Door, Top-Mounted, 90°	33	838	SXDRB33L1US
Left-Hinged Locking Door, Top-Mounted, 90°	33	838	SXDRB33L1TS
Left-Hinged Locking Door, 270°	33	838	SXDRB33L2BS
Left-Hinged Non-Locking Door, 270°	33	838	SXDRB33L2NS
Left-Hinged Non-Locking Door, Top-Mounted, 270°	33	838	SXDRB33L2US
Left-Hinged Locking Door, Top-Mounted, 270°	33	838	SXDRB33L2TS
Right-Hinged Locking Door, 90°	33	838	SXDRB33R1BS
Right-Hinged Non-Locking Door, 90°	33	838	SXDRB33R1NS
Right-Hinged Non-Locking Door, Top-Mounted, 90°	33	838	SXDRB33R1US
Right-Hinged Locking Door, Top-Mounted, 90°	33	838	SXDRB33R1TS
Right-Hinged Locking Door, 270°	33	838	SXDRB33R2BS
Right-Hinged Non-Locking Door, 270°	33	838	SXDRB33R2NS
Right-Hinged Non-Locking Door, Top-Mounted, 270° Right-Hinged Locking Door, Top-Mounted, 270°	33 33	838 838	SXDRB33R2US SXDRB33R2TS
Center-Closing Locking Door, 90°	36	915	SXDRB36C1BS
Center-Closing Non-Locking Door, 90° Center-Closing Non-Locking Door, Top-Mounted, 90°	36 36	915 915	
Center-Closing Locking Door, Top-Mounted, 90°	36	915	
Center-Closing Locking Door, 270° Center-Closing Non-Locking Door, 270°	36 36	915 915	SXDRB36C2BS SXDRB36C2NS
Center-Closing Non-Locking Door, Top-Mounted, 270		915	
Center-Closing Locking Door, Top-Mounted, 270°	36	915	SXDRB36C2TS
Left-Hinged Locking Door, 90°	36	915	SXDRB36L1BS
Left-Hinged Non-Locking Door, 90°	36	915	SXDRB36L1NS
Left-Hinged Non-Locking Door, Top-Mounted, 90°	36	915	
Left-Hinged Locking Door, Top-Mounted, 90°	36	915	SXDRB36L1TS
Left-Hinged Locking Door, 270°	36	915	SXDRB36L2BS
Left-Hinged Non-Locking Door, 270°	36	915	SXDRB36L2NS
Left-Hinged Non-Locking Door, Top-Mounted, 270°	36	915	SXDRB36L2US
Left-Hinged Locking Door, Top-Mounted, 270°	36	915	SXDRB36L2TS
Right-Hinged Locking Door, 90°	36	915	SXDRB36R1BS
Right-Hinged Non-Locking Door, 90°	36	915	
Right-Hinged Non-Locking Door, Top-Mounted, 90°	36	915	SXDRB36R1US
Right-Hinged Locking Door, Top-Mounted, 90°	36	915	SXDRB36R1TS
Right-Hinged Locking Door, 270°	36	915	SXDRB36R2BS
Right-Hinged Non-Locking Door, 270°	36	915	SXDRB36R2NS
Right-Hinged Non-Locking Door, Top-Mounted, 270°	36	915	
Right-Hinged Locking Door, Top-Mounted, 270°	36	915	SXDRB36R2TS






Left-hinged door



hinged doors



One left-hinged and two right-hinged doors




Starsys[™] Doors — Clear

Olaroyo Dooro		C	noui
Description		ght	Cat. No.
Description	(m.) 24	(mm)	SXDRB24C1BC
Center-Closing Locking Door, 90°		610	
Center-Closing Non-Locking Door, 90°	24		SXDRB24C1NC
Center-Closing Non-Locking Door, Top-Mounted, 90°			SXDRB24C1UC
Center-Closing Locking Door, Top-Mounted, 90°	24	610	SXDRB24C1TC
Center-Closing Locking Door, 270°	24	610	SXDRB24C2BC
Center-Closing Non-Locking Door, 270°	24	610	SXDRB24C2NC
Center-Closing Non-Locking Door, Top-Mounted, 270	°24	610	SXDRB24C2UC
Center-Closing Locking Door, Top-Mounted, 270°	24	610	SXDRB24C2TC
Left-Hinged Locking Door, 90°	24	610	SXDRB24L1BC
Left-Hinged Non-Locking Door, 90°	24	610	
Left-Hinged Non-Locking Door, Top-Mounted, 90°	24	610	
Left-Hinged Locking Door, Top-Mounted, 90°	24	610	SXDRB24L1TC
	04		
Left-Hinged Locking Door, 270°	24	610 610	SXDRB24L2BC
Left-Hinged Non-Locking Door, 270°			SXDRB24L2NC
Left-Hinged Non-Locking Door, Top-Mounted, 270°	24		SXDRB24L2UC
Left-Hinged Locking Door, Top-Mounted, 270°	24	610	SXDRB24L2TC
Right-Hinged Locking Door, 90°	24	610	SXDRB24R1BC
Right-Hinged Non-Locking Door, 90°	24	610	SXDRB24R1NC
Right-Hinged Non-Locking Door, Top-Mounted, 90°	24	610	SXDRB24R1UC
Right-Hinged Locking Door, Top-Mounted, 90°	24	610	SXDRB24R1TC
Right-Hinged Locking Door, 270°	24	610	SXDRB24R2BC
Right-Hinged Non-Locking Door, 270°	24		SXDRB24R2NC
Right-Hinged Non-Locking Door, Top-Mounted, 270°	24	610	
Right-Hinged Locking Door, Top-Mounted, 270°	24	610	
Center-Closing Locking Door, 90°	27		SXDRB27C1BC
Center-Closing Non-Locking Door, 90°	27		SXDRB27C1NC
Center-Closing Non-Locking Door, Top-Mounted, 90°	27		SXDRB27C1UC
Center-Closing Locking Door, Top-Mounted, 90°	27	686	SXDRB27C1TC
Center-Closing Locking Door, 270°	27	686	SXDRB27C2BC
Center-Closing Non-Locking Door, 270°	27	686	SXDRB27C2NC
Center-Closing Non-Locking Door, Top-Mounted, 270	°27	686	SXDRB27C2UC
Center-Closing Locking Door, Top-Mounted, 270°	27	686	SXDRB27C2TC
Left-Hinged Locking Door, 90°	27	686	SXDRB27L1BC
Left-Hinged Non-Locking Door, 90°	27	686	
Left-Hinged Non-Locking Door, Top-Mounted, 90°	27	686	
Left-Hinged Locking Door, Top-Mounted, 90°	27	686	
Left-Hinged Locking Door, 270°	27	686	
Left-Hinged Non-Locking Door, 270°	27	686	
Left-Hinged Non-Locking Door, Top-Mounted, 270°	27	686	SXDRB27L2UC
Left-Hinged Locking Door, Top-Mounted, 270°	27	686	SXDRB27L2TC
Right-Hinged Locking Door, 90°	27	686	SXDRB27R1BC
Right-Hinged Non-Locking Door, 90°	27	686	SXDRB27R1NC
Right-Hinged Non-Locking Door, Top-Mounted, 90°	27	686	SXDRB27R1UC
Right-Hinged Locking Door, Top-Mounted, 90°	27	686	SXDRB27R1TC
Right-Hinged Locking Door, 270°	27		SXDRB27R2BC
Right-Hinged Non-Locking Door, 270°	27		SXDRB27R2NC
Right-Hinged Non-Locking Door, Top-Mounted, 270°	27		SXDRB27R2UC
Right-Hinged Locking Door, Top-Mounted, 270°	27	686	SXDRB27R2TC
Center-Closing Locking Door, 90°	30	760	SXDRB30C1BC
Center-Closing Non-Locking Door, 90°	30	760	SXDRB30C1NC
Center-Closing Non-Locking Door, Top-Mounted, 90°	30	760	SXDRB30C1UC
Center-Closing Locking Door, Top-Mounted, 90°	30	760	SXDRB30C1TC
Center-Closing Locking Door, 270°	30	760	SXDRB30C2BC
Center-Closing Non-Locking Door, 270°	30		SXDRB30C2NC
Center-Closing Non-Locking Door, Top-Mounted, 270			SXDRB30C2UC
Center-Closing Locking Door, Top-Mounted, 270°	30		SXDRB30C2TC
Left-Hinged Locking Door, 90°	30	760	SXDRB30L1BC
Left-Hinged Non-Locking Door, 90°	30	760	
Left-Hinged Non-Locking Door, Top-Mounted, 90°	30	760	SXDRB30L1UC
Left-Hinged Locking Door, Top-Mounted, 90°	30	760	SXDRB30L1TC

Description	Hei (in.)	ght (mm)	Cat. No.
Left-Hinged Locking Door, 270°	30	760	SXDRB30L2BC
Left-Hinged Non-Locking Door, 270°	30	760	SXDRB30L2NC
Left-Hinged Non-Locking Door, Top-Mounted, 270°	30	760	SXDRB30L2UC
Left-Hinged Locking Door, Top-Mounted, 270°	30	760	SXDRB30L2TC
Right-Hinged Locking Door, 90°	30	760	SXDRB30R1BC
Right-Hinged Non-Locking Door, 90°	30	760	
Right-Hinged Non-Locking Door, Top-Mounted, 90°	30	760	
Right-Hinged Locking Door, Top-Mounted, 90°	30	760	SXDRB30R1TC
Right-Hinged Locking Door, 270°	30	760	SXDRB30R2BC
Right-Hinged Non-Locking Door, 270°	30 30	760 760	
Right-Hinged Non-Locking Door, Top-Mounted, 270° Right-Hinged Locking Door, Top-Mounted, 270°	30 30	760	SXDRB30R20C
Center-Closing Locking Door, 90° Center-Closing Non-Locking Door, 90°	33 33	838 838	SXDRB33C1BC SXDRB33C1NC
Center-Closing Non-Locking Door, Top-Mounted, 90°			SXDRB33C1UC
Center-Closing Locking Door, Top-Mounted, 90°	33	838	SXDRB33C1TC
Center-Closing Locking Door, 270°	33	838	SXDRB33C2BC
Center-Closing Non-Locking Door, 270°	33	838	
Center-Closing Non-Locking Door, Top-Mounted, 270)°33	838	
Center-Closing Locking Door, Top-Mounted, 270°	33	838	SXDRB33C2TC
Left-Hinged Locking Door, 90°	33	838	SXDRB33L1BC
Left-Hinged Non-Locking Door, 90°	33	838	SXDRB33L1NC
Left-Hinged Non-Locking Door, Top-Mounted, 90°	33	838	SXDRB33L1UC
Left-Hinged Locking Door, Top-Mounted, 90°	33	838	SXDRB33L1TC
Left-Hinged Locking Door, 270°	33	838	SXDRB33L2BC
Left-Hinged Non-Locking Door, 270°	33	838	SXDRB33L2NC
Left-Hinged Non-Locking Door, Top-Mounted, 270°	33	838	SXDRB33L2UC
Left-Hinged Locking Door, Top-Mounted, 270°	33	838	SXDRB33L2TC
Right-Hinged Locking Door, 90°	33	838	SXDRB33R1BC
Right-Hinged Non-Locking Door, 90°	33	838	SXDRB33R1NC
Right-Hinged Non-Locking Door, Top-Mounted, 90° Right-Hinged Locking Door, Top-Mounted, 90°	33 33	838 838	SXDRB33R1UC SXDRB33R1TC
	33	838	SXDRB33R2BC
Right-Hinged Locking Door, 270° Right-Hinged Non-Locking Door, 270°	33	838	
Right-Hinged Non-Locking Door, Top-Mounted, 270°	33	838	SXDRB33R2UC
Right-Hinged Locking Door, Top-Mounted, 270°	33	838	SXDRB33R2TC
Center-Closing Locking Door, 90°	36	915	SXDRB36C1BC
Center-Closing Non-Locking Door, 90°	36	915	SXDRB36C1NC
Center-Closing Non-Locking Door, Top-Mounted, 90°	36	915	SXDRB36C1UC
Center-Closing Locking Door, Top-Mounted, 90°	36	915	SXDRB36C1TC
Center-Closing Locking Door, 270°	36	915	SXDRB36C2BC
Center-Closing Non-Locking Door, 270°	36	915	SXDRB36C2NC
Center-Closing Non-Locking Door, Top-Mounted, 270			SXDRB36C2UC
Center-Closing Locking Door, Top-Mounted, 270°	36	915	SXDRB36C2TC
Left-Hinged Locking Door, 90°	36	915	SXDRB36L1BC
Left-Hinged Non-Locking Door, 90°	36	915	SXDRB36L1NC
Left-Hinged Non-Locking Door, Top-Mounted, 90° Left-Hinged Locking Door, Top-Mounted, 90°	36 36	915 915	SXDRB36L1UC SXDRB36L1TC
Left-Hinged Locking Door, 270° Left-Hinged Non-Locking Door, 270°	36 36	915 915	SXDRB36L2BC SXDRB36L2NC
Left-Hinged Non-Locking Door, Top-Mounted, 270°	36	915	SXDRB36L2UC
Left-Hinged Locking Door, Top-Mounted, 270°	36	915	SXDRB36L2TC
Right-Hinged Locking Door, 90°	36	915	SXDRB36R1BC
Right-Hinged Non-Locking Door, 90°	36	915	SXDRB36R1NC
Right-Hinged Non-Locking Door, Top-Mounted, 90°	36	915	SXDRB36R1UC
Right-Hinged Locking Door, Top-Mounted, 90°	36	915	SXDRB36R1TC
Right-Hinged Locking Door, 270°	36	915	SXDRB36R2BC
Right-Hinged Non-Locking Door, 270°	36	915	
Right-Hinged Non-Locking Door, Top-Mounted, 270°	36	915	SXDRB36R2UC
Right-Hinged Locking Door, Top-Mounted, 270°	36	915	SXDRB36R2TC



One pair center-closing doors for double-wide bays (with no center post)



One pair of centerclosing doors & one right-hinged door.



Double-Wide Overhead Cabinet shown with Clear Doors



Solid Door

Drawer and Door Label Kit

10 per package. 1" (25mm) H. x 16" (406mm) L. Cat. No. **SXLABKIT**





Preconfigured Mobile WorkCenters with Black Epoxy Tops

0				
Description	Cat. No.	Overall Dimensions Width/Length/Height	Cat. No. With Overhead	Overall Dimensions Width/Length/Height
ingle-Wide Units				
Single-Wide Heavy-Duty 12" (305mm) (2)	SXMWS33EBS1	28.6x23.6x33.5		
Single-Wide with Standard Drawers	SXMWS33EBS2	28.6x23.6x33.5		
Single-Wide with Standard Drawers	SXMWS36EBS2	28.6x23.6x36.5	SXMWS36EOH2	28.6x23.6x81.5
Single-Wide with Locking Drawers and Poly Shelves	SXMWS36EBS3	28.6x23.6x36.5	SXMWS36EOH3	28.6x23.6x81.5
Single-Wide with Locking Drawers and Wire Shelves	SXMWS36EBS4	28.6x23.6x36.5	SXMWS36EOH4	28.6x23.6x81.5
Single-Wide with Standard Drawers	SXMWS39EBS2	28.6x23.6x39.5	SXMWS39EOH2	28.6x23.6x81.5
Single-Wide with Locking Drawers and Poly Shelves	SXMWS39EBS3	28.6x23.6x39.5	SXMWS39EOH3	28.6x23.6x81.5
Single-Wide with Locking Drawers and Wire Shelves	SXMWS39EBS4	28.6x23.6x39.5	SXMWS39EOH4	28.6x23.6x81.5
ouble-Wide Units				
Double-Wide Heavy-Duty 12" (305mm) (2)	SXMWD33EBS1	28.6x43.4x33.5		
Double-Wide with Standard Drawers	SXMWD33EBS2	28.6x43.4x33.5		
Double-Wide with Standard Drawers	SXMWD36EBS2	28.6x43.4x36.5	SXMWD36EOH2	28.6x43.4x81.5
Double-Wide with DHD Drawers	SXMWD36EBS5	28.6x43.4x36.5	SXMWD36EOH5	28.6x43.4x81.5
Double-Wide with Locking Drawers and Poly Shelves	SXMWD36EBS3	28.6x43.4x36.5	SXMWD36EOH3	28.6x43.4x81.5
Double-Wide with Locking Drawers and Wire Shelves	SXMWD36EBS4	28.6x43.4x36.5	SXMWD36EOH4	28.6x43.4x81.5
Double-Wide with Standard Drawers	SXMWD39EBS2	28.6x43.4x39.5	SXMWD39EOH2	28.6x43.4x81.5
Double-Wide with DHD Drawers	SXMWD39EBS5	28.6x43.4x39.5	SXMWD39EOH5	28.6x43.4x81.5
Double-Wide with Locking Drawers and Poly Shelves	SXMWD39EBS3	28.6x43.4x39.5	SXMWD39EOH3	28.6x43.4x81.5
Double-Wide with Locking Drawers and Wire Shelves	SXMWD39EBS4	28.6x43.4x39.5	SXMWD39EOH4	28.6x43.4x81.5
riple-Wide Units				
Triple-Wide with Standard Drawers	SXMWT36EBS2	28.6x63.2x36.5	SXMWT36EOH2	28.6x63.2x81.5
Triple-Wide with S & D HD Drawers	SXMWT36EBS6	28.6x63.2x36.5	SXMWT36EOH6	28.6x63.2x81.
Triple-Wide with Locking Drawers and Poly Shelves	SXMWT36EBS3	28.6x63.2x36.5	SXMWT36EOH3	28.6x63.2x81.
Triple-Wide with Locking Drawers and Wire Shelves	SXMWT36EBS4	28.6x63.2x36.5	SXMWT36EOH4	28.6x63.2x81.5
Triple-Wide with Standard Drawers	SXMWT39EBS2	28.6x63.2x39.5	SXMWT39EOH2	28.6x63.2x81.5
Triple-Wide with S & D HD Drawers	SXMWT39EBS6	28.6x63.2x39.5	SXMWT39EOH6	28.6x63.2x81.5
Triple-Wide with Locking Drawers and Poly Shelves	SXMWT39EBS3	28.6x63.2x39.5	SXMWT39EOH3	28.6x63.2x81.5
Triple-Wide with Locking Drawers and Wire Shelves	SXMWT39EBS4	28.6x63.2x39.5	SXMWT39EOH4	28.6x63.2x81.5
Triple Kneewell with Standard Drawers	SXMWTK36EBS2	28.6x63.2x36.5	SXMWTK36EOH2	28.6x63.2x81.5
Triple Kneewell with Locking Drawers and Poly Shelves	SXMWTK36EBS3	28.6x63.2x36.5	SXMWTK36EOH3	28.6x63.2x81.5
Triple Kneewell with Locking Drawers and Wire Shelves	SXMWTK36EBS4	28.6x63.2x36.5	SXMWTK36EOH4	28.6x63.2x81.
Triple Kneewell with Standard Drawers	SXMWTK39EBS2	28.6x63.2x39.5	SXMWTK39EOH2	28.6x63.2x81.
Triple Kneewell with Locking Drawers and Poly Shelves	SXMWTK39EBS3	28.6x63.2x39.5	SXMWTK39EOH3	28.6x63.2x81.
Triple Kneewell with Locking Drawers and Wire Shelves	SXMWTK39EBS4	28.6x63.2x39.5	SXMWTK39EOH4	28.6x63.2x81.
Single Kneewell with HD Drawers	SXMWSK33EBS1	28.6x73x33.5		
Single Kneewell with Standard Drawers	SXMWSK36EBS2	28.6x73x36.5		
Single Kneewell with Locking Drawers and Poly Shelves	SXMWSK36EBS3	28.6x73x36.5		
Single Kneewell with Locking Drawers and Wire Shelves	SXMWSK36EBS4	28.6x73x36.5		
Single Kneewell with Standard Drawers	SXMWSK39EBS2	28.6x73x39.5		
Single Kneewell with Locking Drawers and Poly Shelves	SXMWSK39EBS3	28.6x73x39.5		

Note: Above units include taupe door and/or drawer pulls

Note: Mobile units include 5" (127mm) poly plate casters (2 toe brake, 2 swivel). Refer to next page for other caster options. Overhead units include a 27" (686mm) overhead cabinet with locking clear doors and two poly shelves. If additional poly shelves are required, please use Catalog Number shown on page 3. All tops are black epoxy resin. Colored laminate and other top materials are available on request. Contact your Metro representative for more information.

Preconfigured Mobile WorkCenter Units with Blue Laminate Tops

SXSENT1	28.6x23.6x81.5
SXDENT2	28.6x43.4x81.5
SXD40MW10	28.6x43.4x81.5
SXD40MW12	28.6x43.4x81.5
SXD40MW13	28.6x43.4x81.5
SXT38MW14	28.6x63.2x79.6
SXK32MW5	28.6x73x31.9
SXK32MW6	28.6x73x31.9
SXK41MW7	28.6x73x40.3
SXK41MW8	28.6x73x40.3
	SXDENT2 SXD40MW10 SXD40MW12 SXD40MW13 SXT38MW14 SXK32MW5 SXK32MW6 SXK41MW7

Note: Above units, where appropriate, include a slate blue countertop along with slate blue door and/or drawer pulls. Note: Laminate top material is 1¹/₈" (29mm) Chip Core with HPL. Laminate thickness is .04" (1.0mm). Phenolic backer thickness is .02" (0.5mm).



Starsys Mobile Workcenter units shown below include epoxy countertops. Other countertop options are also available including Trespa Phenolic, Stainless Steel, Laminate and Corian[®] Contact your Metro representative for more information.



Caster Options

5 (127mm) polyurethane plate casters come standard with preconfigured units (shown above) and make units easy to maneuver in tight spaces. Other caster options are listed on page 4.

Starsys Carts are built to exact customer specifications, therefore, they are non-cancelable, non-returnable.