TIM CAMPBELL 800-400-7500



Item#

Job




SUPER WIDE[™] SHELVING

- Cost Effective: Super Wide[™] shelves eliminate the posts, hooks, and extra shelves required in conventional applications, meaning greater cost effectiveness.
- **High-Density Storage:** Super Wide[™] shelves have a greater storage capacity for holding large quantities of supplies, especially large, bulky objects, providing maximum storage in minimum space.
- Super Wide[™] Shelves are available in 30" (760mm) and 36" (910mm) widths, and in 36" (910mm), 48" (1220mm), 60" (1525mm), and 72" (1825mm) lengths.
- Shelf Accessibility: Shelves can be loaded/unloaded easily from all sides. The larger width eliminates intermediate posts needed when narrower shelves are combined.
- **Unique Design:** The open wire design of these heavy-gauge shelves minimizes dust accumulation and allows a free circulation of air, greater visibility of stored items and greater light penetration.
- Versatile Construction: Super Wide[™] shelving can change as quickly as your needs change. By using various accessories, hundreds of shelving configurations become possible.
- Fast Assembly Time: Super Wide[™] shelves allow for faster assembly time because fewer shelves and posts are needed.
- Fast, Secure Assembly: Post has rolled, circular grooves along its entire length at 1" (25mm) intervals. A patented, tapered split sleeve (plastic or aluminum) snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves providing a positive lock. Shelf is assembled in minutes without the use of any special tools.
- Shelf Ribs: Run front to back, allowing you to slide items on and off shelves smoothly and quickly.
- Adjustability: Shelves can be adjusted at 1" (25mm) intervals along the entire height of the numbered post.
- **Durable:** Super Wide[™] shelving is available in chrome stainless and Metroseal II[™] finishes.
- Adjustable Feet: Bolt levelers compensate for surface irregularities.



DIMENSIONS Shelves

Width		Length			orox. I. Wt.	Cat. No.	Cat. No.	Cat. No.
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	Chrome	Metroseal II	Stainless
30	760	36	910	15	6.8	3036NC	3036NK2	3036NS
30	760	48	1220	21	9.5	3048NC	3048NK2	3048NS
30	760	60	1525	26 ¹ / ₂	11.7	3060NC	3060NK2	3060NS
30	760	72	1825	31	14.0	3072NC	3072NK2	3072NS
36	910	36	910	18	8.2	3636NC	3636NK2	3636NS
36	910	48	1220	23	10.4	3648NC	3648NK2	3648NS
36	910	60	1525	29	13.1	3660NC	3660NK2	3660NS
36	910	72	1825	34 ^{1/} ₂	15.6	3672NC	3672NK2	3672NS



Metro®


Posts

Heid	aht*	App Pkd.		Cat. No.	Cat. No.	Cat. No.
(in.)	(mm)	(lbs.)	(kg)	Chrome	Metroseal II	Stainless
7 ⁵ / ₈	194	1/2	.23	7P		
14 ¹ / ₂	370	1	0.5	13P	13PK2	13PS
				27P		27PS
34 ^{1/2}	877	2	0.9	33P	33PK2	33PS
54 ⁹ / ₁₆	1386	3	1.4	54P	54PK2	54PS
62 ⁹ /16	1589	3 ¹ / ₂	1.6	63P	63PK	63PS
74 ⁵ / ₈	1895	4	1.8	74P	74PK2	74PS
865/8	2200	5	2.3	86P	86PK2	86PS




*Height include leveling bolt and cap.

ACCESSORIES




Shelf Dividers

Shelf	Width	Cat. No.
(in.)	(mm)	Chrome
30	760	DD30C
36	910	DD36C



1" (25mm) Ledges

· · - • · · ·			
Le	ngth	Cat. No.	
(in.)	_ (mm)	Chrome	
30	760	L30N-1C	
36	910	L36N-1C	
 48	1220	L48N-1C	
60	1525	L60N-1C	
72	1825	L72N-1C	
		-	



4" (102mm) Ledges

Le	ngth	Cat. No.
(in.)	(mm)	Chrome
30	760	L30N-4C
36	910	L36N-4C
48	1220	L48N-4C
60	1525	L60N-4C
72	1825	L72N-4C



POST CLAMP Cat. No. 9994Z



"S" HOOKS Used to "add-on" shelving units with only two posts required. Cat. No. 9995Z

đ

STEM CASTERS

For more informaton, refer to catalog sheet #11.20.