TIM CAMPBELL 800-400-7500



Job	 			

Central Sterile Productivity Bench

This productivity bench provides a clean, obstruction-free surface for the preparation of surgical instrument trays and surgical packs and an optional accessory grid for tools and materials required.

Features Include:

- Adjustable legs, footrest or shelf to help reduce worker fatique.
- Adjustable work surface height is from 31"-37" (787-940mm) on 1" (25mm) increments.
- Type 304 stainless steel or plastic laminate work surface.
- Rounded corners to reduce injury and torn packs.
- Posts are HD 1¹/₂" (38mm) diameter 16 gauge powder coated steel.
- Wide range of accessories to customize by need.



Basic models consist of: (shown above with stainless steel top)

- Two short front posts and two tall rear posts with accessory slots.
- Stainless steel or plastic laminate work surface.
- Support frame(s): bottom three-sided* and top tie-bar.
- Choice of solid bottom shelf or foot rest frame. *Required with stainless steel top only.

Basic Model with Stainless Steel Work Surface*

Depth x Width			Approx. Pkd. Wt.					
(in.)	(mm)	Description	(lbs.)	(kg)	Cat. No.			
30x72	762x1829	72" (1829mm) Bench with Flat Bottom Shelf	257	116	PBH3072FS			
30x72	762x1829	72" (1829mm) Bench with H-Frame Footrest	238	107	PBH3072HS			
30x96	762x2438	96" (2438mm) Bench with Flat Bottom Shelf	291	131	PBH3096FS			
30x96	762x2438	96" (2438mm) Bench with H-Frame Footrest	272	123	PBH3096HS			
Basic Model with Laminate Work Surface*								
32 ¹ / ₄ x60	820x1525	60" (1525mm) Bench with H-Frame Footrest	138	62	PBH3060L			
32 ¹ / ₄ x72	820x1829	72" (1829mm) Bench with H-Frame Footrest	151	68	PBH3072L			

^{*}Actual work surface depth is 30" (762mm).

Work surface weight capacity is 1,000 lbs. (453kg) evenly distributed.

Accessories

Stainless Steel Work Surface Mounted

Width x Length x Helght			App Pkd.		
(in.)	(mm)	Description	(lbs.)	(kg)	Cat. No.
14 ¹ / ₄ x28x5 ³ / ₄	362x711x146	Economy Polymer Drawer	7	3	WTD21C
24x25 ³ / ₄ x7 ¹ / ₂	610x654x191	Stainless Deluxe Drawer	31	14	WTD51S*
*WTD51S is stackabl	e.				

Plastic Laminate Work Surface Mounted

12x19 ¹ / ₂ x5 ³ / ₄	305x495x146	6" (152mm) Starter Locking Drawer	17	8	PBA-SD6DL
12x19 ¹ / ₂ x5 ³ / ₄	305x495x146	6" (152mm) Add-on Locking Drawer	16	7	PBA-AD6DL
12x19 ¹ / ₂ x10 ³ / ₄	305x495x273	12" (305mm) Starter Locking Drawer	22	10	PBA-SD12DL
12x19 ¹ / ₂ x10 ³ / ₄	305x495x273	12" (305mm) Add-on Locking Drawer	21	10	PBA-AD12DL

Add-on drawers can be added to 6" (152mm) starter only. If 12" (305mm) starter drawer is selected no other drawer can be added.

CENTRAL STERILE PRODUCTIVITY BENCH



Accessories **Post Mounted**

gth x Helght	Approx. Pkd. Wt.				
(mm)	Description	(lbs.)	(kg)	Cat. No.	
305x1525x31	(A) Adjustable Cantilever Shelf	13	5.9	PBA-1260Q ¹	
35x1467x41	(B) Power Outlet Strip	4	1.8	PBA-60PQ ²	
305x1397x76	(C) Light Assembly	26	11.7	PBA-LA60 ³	
13x1467x76	Bin Rail	10	4.5	PBA-BBCQ	
1467x838	Full Height Grid with Clips	21	9.5	PBA-GPCQ⁴	
455x1525	(D) Half Height Grid	14	6.3	WG1860BR⁴†	
	(E) Grid Clips (package of 4)	.3	.1	9985QS [†]	
	(E) Grid Clip Locks (package of 4)	.3	.1	9985QSL [†]	
	(mm) 305x1525x31 35x1467x41 305x1397x76 13x1467x76 1467x838	(mm) Description 305x1525x31 (A) Adjustable Cantilever Shelf 35x1467x41 (B) Power Outlet Strip 305x1397x76 (C) Light Assembly 13x1467x76 Bin Rail 1467x838 Full Height Grid with Clips 455x1525 (D) Half Height Grid (E) Grid Clips (package of 4)	gth x Helght (mm) Description Pict (lbs.) 305x1525x31 (A) Adjustable Cantilever Shelf 13 35x1467x41 (B) Power Outlet Strip 4 305x1397x76 (C) Light Assembly 26 13x1467x76 Bin Rail 10 1467x838 Full Height Grid with Clips 21 455x1525 (D) Half Height Grid 14 (E) Grid Clips (package of 4) .3	gth x Helght (mm) Description Pkd. Wt. (lbs.) Wt. (lbs.) (kg) 305x1525x31 (A) Adjustable Cantilever Shelf 13 5.9 35x1467x41 (B) Power Outlet Strip 4 1.8 305x1397x76 (C) Light Assembly 26 11.7 13x1467x76 Bin Rail 10 4.5 1467x838 Full Height Grid with Clips 21 9.5 455x1525 (D) Half Height Grid 14 6.3 (E) Grid Clips (package of 4) .3 .1	

[†] Requires 1 - 9985QS and 1 - 9985QSL.

Grid Mounted

Width x Length x Helght		Approx. Pkd. Wt.				
(in.)	(mm)	Description	(lbs.)	(kg)	Cat. No.	
9x18 ¹ / ₂	228x470	(F) Grid Shelf	4	2	PBA-GSD⁵	
16 ³ / ₄ x16 ³ / ₄	425x425	(G) Monitor Shelf	6	3	PBA-MS⁵	
12 ¹ / ₂ x6 ¹ / ₄	317x159	Hanging File Holder	3	1	PBA-PFH	
2x9	50x228	(H) Catalog/File Holder	3	1	PBA-CHD	
11 ³ / ₄ x3	298x76	(I) Short Bin Holder	2	1	PBA-1BH	
22 ¹ / ₄ x3	565x76	Long Bin Holder	3	1	PBA-2BH	
5 ¹ / ₂ x11x5	140x279x127	(J) Small Bin	12	5	MB30230B ⁶	
11x11x5	279x279x127	Large Bin	9	4	MB30230B ⁷	
3 ¹ / ₄ x2x3 ¹ / ₂	95x51x89	Double Hook	.2	.1	HK26C	

- Weight capacity = 100 lbs. (45kg) evenly distributed.
 6 outlets, 115V, 15A, 60Hz, illuminated power switch, 15 amp fuse.
 UL Listed, accepts 2 48" (1220mm), 40W fluorescent bulbs, not included.
 Weight capacity = 250 lbs. (13kg) total (including all accessories and bins).
 Weight capacity = 50 lbs. (23kg) evenly distributed.
- ⁶ Order in multiples of 12
- Order in multiples of 6. В

Components:

- 1 Stainless work surface
- 2 Laminate work surface
- 3 Tie Bar
- 4 3-Sided support frame*
- 5 Galvanized bottom shelf
- 6 Foot rest
- *3-sided support frame is required on benches with Stainless steel top only.

